



SDC-108 衛星一分歧器



SDC-212 衛星二分歧器



SDC-412 衛星四分歧器

規格:

型號		SDC-108	SDC-212	SDC-412	
頻率範圍		5~2350MHz	5~2350MHz	5~2350MHz	
幹線損失	5~76MHz	2.5	2.7	2.7	
	76~222MHz	2.2	2.5	2.5	
	222~770MHz	2.5	2.5	3.0	
	770~1489MHz	4.0	4.5	4.0	
	1489~2150MHz	6.0	6.0	6.0	
	2150~2602MHz	7.0	7.0	8.0	
支線損失	5~76MHz	8.0	12.0	12	
	76~222MHz	8.0	11.5	12	
	222~770MHz	8.0	12.0	14	
	770~1489MHz	8.5	13.0	13	
	1489~2150MHz	9.0	14.0	13.5	
	2150~2602MHz	9.5	15.0	18	
反射 損 失	IN	5~76MHz	12.0	12.0	10.0
		76~222MHz	15.0	14.0	12.0
		222~770MHz	15.0	14.0	12.0
		770~1489MHz	12.0	12.0	12.0
		1489~2150MHz	10.0	12.0	12.0
		2150~2602MHz	8.0	9.0	7.0
	OUT	5~76MHz	15.0	15.0	12.0
		76~222MHz	20.0	20.0	25.0
		222~770MHz	15.0	15.0	15.0
		770~1489MHz	15.0	15.0	15.0
		1489~2150MHz	15.0	15.0	15.0
		2150~2602MHz	8.0	8.0	9.0
隔離度	5~76MHz	22.0	15.0	20.0	
	76~222MHz	23.0	25.0	25.0	
	222~770MHz	20.0	20.0	22.0	
	770~1489MHz	20.0	18.0	20.0	
	1489~2150MHz	18.0	18.0	18.0	
	2150~2602MHz	18.0	15.0	18.0	
駐波比 V.S.W.R	5~76MHz	1.8	1.8	2.1	
	76~222MHz	1.5	1.6	1.8	
	222~770MHz	1.5	1.6	1.8	
	770~1489MHz	1.8	1.8	1.8	
	1489~2150MHz	2.1	1.8	1.8	
	2150~2602MHz	2.4	2.2	2.8	
尺寸(不含接頭)長*寬*高		5.2*6.0*2.3CM	5.2*6.0*2.3CM	7.5*6.0*2.3CM	
阻抗		75Ω			